



Technology that connects



Electric Handscrewdriver ESE

For small screws and simple screwdriving tasks

Electric Handscrewdriver

ESE

Handy: For small screws and simple screwdriving tasks

ESE

simple handscrewdriver with control

Contents of delivery:

- _ 1 electric screwdriver with power supply incl. 2,4 m cable
- _ 2 x 1/4"-quick-change bit PH1 PH2
- _ start button
- _ adjustable torque
- _ optional: ESD grip



Electric Handscrewdriver ESE 2.0



Technical Data ESE

Push-start	Button-start	Drive	Torque range Nm	Weight approx. kg	Diameter approx. mm	Length approx. mm (without Bit)
	ESE 0.9	650	0,2 - 0,9	0,31	32	204
	ESE 2.0	700	0,7 - 2,0	0,72	39	257
	ESE 3.0	500	1,2 - 3,0	0,72	39	257

Attention : to avoid motor overheating and eventually overload especially for thread forming or thread cutting applications, you have to choose a duty cycle of approx. 30% (1 sec operation / 3 sec rest)

Technical Data Power Supply

for type	Input Voltage in V	Output Voltage in V	Dimensions LxWxH in mm
ESE 0.9	220-240 V/50 Hz oder 100-120 V/60 Hz	DC 35 V	132 x 69 x 42
ESE 2.0 - 3.0	220-244 V/50 Hz oder 100-120 V/60 Hz	DC 30 V	154 x 84 x 52



Technology that connects

Weber Schraubautomaten GmbH

Hans-Urmiller-Ring 56
D-82515 Wolfratshausen
Tel.: +49 (8171) 406-0
Fax: +49 (8171) 406-111
info@weber-online.com
www.weber-online.com